

Price List - Wireless Video and Monitor Products from Shimbol

version 24.6

valid 19 June 2024

www.zeroone-video.com



Product Name	Description	Code	MSRP
Wireless Devices			
Shimbol ZO600M	5.5 inch HDMI touch screen monitor with user selectable TX or RX 180m LOS	zo001	€399.00
Shimbol ZO600MS	Dual -Band 1000FT 5.5 inch Touchscreen 3D Lut HDMI 3G- SDI Wireless recording	zo005	€519.00
Shimbol ZO1000	TX+RX set for SDI and HDMI video 300m LOS	zo002	€499.00
Shimbol ZO1000 RX	RX for SDI and HDMI video 300m LOS	zo006	€249.50
Shimbol ZO600S	TX+RX set for SDI and HDMI video 180m LOS	zo003	€419.00
Shimbol ZO500	TX+RX set for HDMI video 150m LOS	zo004	€379.00
TP Mini	TX+RX set for HDMI video 180m LOS	zo007	€89.00
Recording Monitors			
Shimbol Memory I	5.5 inch 4K HDMI Video Recording Monitor, 1920*1080 Touchscreen, 2000 nits, 3	zo010	€279.00
Shimbol Memory I Pro	5.5 inch 4K HDMI+3G- SDI Video Recording Monitor, 1920*1080 Touchscreen, 20	zo011	€459.00
Shimbol Memory 7 Pro	7 inch 4K HDMI+3G- SDI Video Recording Monitor, 1920*1080 Touchscreen, 2200	zo012	€479.00
On-camera Monitors			
Shimbol M5	5.5 inch Professional on-camera monitor, 1920*1080, 1200 nits, Touchscreen, 3D	zo020	€169.00
Shimbol M7	7 inch Professional on-camera monitor, 1920*1080 2000 nits, Touchscreen , 3D L	zo021	€379.00

NPF Batteries + Charger

You can purchase the following NPF batteries plus Charger from us, suitable for all Shimbol products

DGT-F970 Sony NP-F970 compatible	7.4V - 6.6Ah - 48.8Wh	dg020	€56.00
DGT-F980D Sony NP-F980 compatible,	2DC 7.4V - 8.8Ah - 65.1Wh	dg021	€68.00
DGT-NP-F550 570 Sony NP-F550 570 comp	7.4V - 2.2Ah - 16.3Wh	dg025	€22.00
Indipro NP-F Series Dual Battery Charger		ip041	€32.00

Mail your order to orders@mediamachine.nl

Mediamachine, Hazepad 43, 1544 PW Zaandijk, The Netherlands, Phone +31 75 6572290.

All prices are ex VAT and freight costs.

Specs Shimbol ZO600M



Description	600FT 5.5 inch
Screen Size	5.5 inch Touchs
Resolution	1920*1080
Contrast Ratio	1200:1
Brightness	1000cd/m2
Interface	1* HDMI input/
Power SupplyWay/Voltag	Sony NP-F serie
Voltage	7-16.8V
Power Consumption	<8W
Video Input Format	1920*1080p60/
	1920*1080i60/!
Video Recording Format	MP4 (a single fi
Teleprompter File Format	TXT
LUT+Format	Cube(17*17*17
Transmission Frequency Band	5G
Modulation Mode	OFMD
Transmission Power/Receiving Sensitivity	Maximum 17dB
Band Width	20MHZ
Audio+Frequency	48KHZ
Occupied Bandwidth	20/40MHz
Latency	Min 0.08S
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Unit Size(mm)	146.6*87.6*26.
Unit+WeightUnit Weight	300g
Advanced+Features	Teleprompter, S
In the box:	Monitor, After-s

Packaging: Color box size

Wireless features

195.5 * 142.5 *

- Built-in Antenn
- Real-time app
- Simultaneousl
- Transmits up 1
- 500ft/150m lii
- Extremely Lov

Specs Shimbol ZO600MS



Description	Shimbol ZO600M
Screen Size	5.5 inch Touchs
Resolution	1920*1080
Contrast Ratio	1200:1
Brightness	2000cd/m2
Interface	1* HDMI and SI
Power SupplyWay/Voltag	Sony NP-F serie
Voltage	DC6.5V-16.8V
Power Consumption	<13W
Video Input Format	1920*1080p60/ 1920*1080i60/5
Video Recording Format	1280*720p60/5
LUT+Format	MP4 (a single fi Cube(17*17*17
Transmission Frequency Band	2.4G&5G
Modulation Mode	OFMD
Transmission Power/Receiving Sensitivity	Maximum 17dB
Band Width	20MHZ
Audio+Frequency	48KHZ
Occupied Bandwidth	20/40MHz

Latency	Min 0.08S
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Unit Size(mm)	151*103*29.5
Unit+WeightUnit Weight	340g
Advanced+Features	Scope Menu, sa
In the box:	Monitor, After-s
	5× Antennas, M
Packaging: Color box size	
Wireless features	<ul style="list-style-type: none"> • Real-time app • Simultaneousl • Transmits up t • 1000ft/300m • Extremely Lov

Specs Shimbol ZO1000



- Transmits up to 1080p60 SDI or HDMI video
- 1000ft/300m line-of-sight transmission to receiver
- Transmitter: HDMI In, SDI In, Receiver: HDMI Out & SDI Out + USB-C output (Embedded UVC)
- Metal Housings with 1/4"-20 mounting thread
- Bright OLED Display
- Real-time app monitoring via the Shimbol app
- Simultaneously transmit to two receivers and one app
- Power via Sony NP-F series battery or USB Type-C input
- Extremely Low 0.08s Latency
- * In the box: Transmitter, Receiver, User Manual, USB-C cable
- Packaging: Color box , size :114.2 * 152.4 * 78 mm ; Weight , 530g ;

Specs Shimbol Z0600S

Transmitter



Receiver



- Transmits up to 1080p60 SDI or HDMI video
- 600ft/180m line-of-sight transmission to receiver
- Transmitter: HDMI In, SDI In, Receiver: HDMI Out & SDI Out
- Metal Housings with 1/4"-20 mounting thread
- Built-in Antennas
- Bright OLED Display
- Real-time app monitoring via the Shimbol app
- Simultaneously transmit to two receivers and one app
- Power via Sony NP-F series battery (without battery inside), or USB Type-C input
- Extremely Low 0.1s Latency
- In the box: Transmitter; Receiver; User Manual; USB-C cable
- Packaging: Color box size , 114.2 * 152.4 * 78 mm ; Weight , 510g

Specs Shimbol Z0500

Transmitter



Receiver



- Transmits up to 1080p60 HDMI video
- 500ft/150m line-of-sight transmission to receiver
- Transmitter: HDMI In, HDMI Out, Receiver: 2x HDMI Out
- Metal Housings with 1/4"-20 mounting thread
- Built-in Antennas
- Bright OLED Display
- Real-time app monitoring via the Shimbol app
- Simultaneously transmit to two receivers and one app
- Power via Sony NP-F series battery (without battery inside), or USB Type-C input
- * Extremely Low 0.1s Latency
- * In the box: Transmitter; Receiver, User Manual, USB-C cable
- * Packaging: Color box size, 131 * 97.5 * 81.5 mm

Specs TP MINI



- * Transmits up to 1080p60 HDMI video
- * 600ft/180m line-of-sight transmission to receiver
- * Transmitter: HDMI In, HDMI Out, Receiver: HDMI Out x 2
- * Metal Housings with 1/4"-20 mounting thread
- * Built-in Antennas
- * Bright OLED Display
- * Power via L-series battery (without battery inside), or USB Type-C input
- * Extremely Low 0.08s Latency
- * In the box: Transmitter x 1; Receiver x 1 ; User Manual x 1; Type C cable x 1
- * Packaging: Color box size, 131 * 97.5 * 81.5 mm

Memory I



Description	5.5 inch 1920*1080
Screen Size	5.5 inch Touchs
Resolution	1920*1080
Contrast Ratio	1200:1
Brightness	2000cd/m2
Interface	1* HDMI input/
Power SupplyWay/Voltag	Sony NP-F serie
Voltage	DC6.5V-16.8V
Power Consumption	<9W
Video Input Format	4096*2160P25/ 3840*2160P30/ 1920*1080p60/ 1920*1080i60/5 1280*720p60/5

Video Recording Format	MP4 (a single f
LUT+Format	Cube(17*17*17
Audio+Frequency	48KHZ
Operating Temperature	-10°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Unit Size(mm)	146.6*87.6*26.
Unit Weight	283g
Advanced+Features	Scope Menu, sa
Standard Accessories	Monitor, Tempe

Memory I Pro



Description	Shimbol 5.5 incl
Screen Size	5.5 inch Touchs
Resolution	1920*1080
Contrast Ratio	1200:1
Brightness	2000cd/m2
Interface	1* HDMI and SI
Power SupplyWay/Voltag	Sony NP-F serie
Voltage	DC6.5V-16.8V
Power Consumption	<12W
Video Input Format	4096*2160P25/ 3840*2160P30/ 1920*1080p60/ 1920*1080i60/5 1280*720p60/5
Video Recording Format	MP4 (a single f
LUT+Format	Cube(17*17*17
Audio+Frequency	48KHZ
Operating Temperature	-10°C ~ 40°C

Storage Temperature
 Unit Size(mm)
 Unit Weight
 Advanced+Features
 Standard Accessories

-20°C ~ 60°C
 146.6*87.6*26.
 320g
 Scope Menu, sa
 Monitor, SD Ca

Memory 7 Pro



Description
 Screen Size
 Resolution
 Contrast Ratio
 Brightness
 Color Gamut
 Viewing Angle
 Interface
 Video Input Format

Shimbal 7 inch :
 7 inch Touchscr
 1920*1080
 1800:1
 2200cd/m2
P3
 170° (H/V)

Video Rec Format
 Lut Format
 Audio+Frequency
 Power Supply Way
 Voltage
 Power Consumption
 Upgrade Method
 LUT Output
 Body material
 Color

1* HDMI and SI
 4096*2160P25/
 3840*2160P30/
 1920*1080p60/
 1920*1080i60/!
 1280*720p60/5
 MP4 (SD card fo
 Cube file (17*1
 48KHZ
 Dual Sony NP-F
 DC7-16V
 <10W
 SD Card
 SDI and HDMI s
 CNC alluminum
 Black

Weight	455g
Size	178.8*110.8*20
Advanced+Features	* Luma Wavefo
Standard Accessories	Monitor, SD Ca

M5



Description	5.5 inch Profess
Screen Size	5 inch Touchscr
Resolution	1920*1080
Contrast Ratio	1200:1
Brightness	1200cd/m2
Interface	1* HDMI input/
Video Input Format	4096*2160P25/ 3840*2160P30/ 1920*1080p60/ 1920*1080i60/5 1280*720p60/5
Lut Format	Cube file (17*1
Audio+Frequency	48KHZ
Power Supply Way	Sony NP-F serie
Voltage	DC6.5-16.8V
Power Consumption	<3.5W
Upgrade Method	SD Card
LUT Output	SDI and HDMI s
Body material	CNC metal farr
Operating Temperature	-10°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Color	Black
Weight	283g
Size	146.6*87.6*26.


Advanced+Features
Standard Accessories

* Luma Wavefo
Monitor, SD Ca

M7



Description	7 inch Professio
Screen Size	7 inch Touchscr
Resolution	1920*1080
Contrast Ratio	1800:1
Brightness	2000cd/m2
Color Gamut	P3
Viewing Angle	170° (H/V)
Interface	1* HDMI and SI
Video Input Format	4096*2160P25/ 3840*2160P30/ 1920*1080p60/ 1920*1080i60/5 1280*720p60/5
Lut Format	Cube file (17*1
Audio+Frequency	48KHZ
Power Supply Way	Dual Sony NP-F
Voltage	DC7-16V
Power Consumption	<10W
Upgrade Method	SD Card
LUT Output	SDI and HDMI s
Body material	CNC alluminum
Color	Blue-gray
Weight	455g
Size	178.8*110.8*20
Advanced+Features	* Luma Wavefo
Standard Accessories	Monitor, SD Ca



Touchscreen 3D Lut Wireless recording Monitor
screen

1* HDMI output / DC power input/ 3.5mm headphone jack/ TF card slot
rechargeable battery + DC Input

59.94/50/30/29. 97/25/24/23.98

59.94/50 1280*720p60/59.94/50

(Storage capacity can't exceed 3.6G)

(Weight: 1733*33*33)

mm

5

Scope Menu, safe frames, grip, ratio marker, zoom, zebra, and many more
includes service card

6 50mm ; Weight , 520g

has


› monitoring via the Shimbol app

› y transmit to two receivers and one app

› to 1080p60 HDMI video

› ne-of-sight transmission to receiver

› v 0.08s Latency



MS Dual-Band 1000FT/300m 5.5 inch Touchscreen 3D Lut HDMI 3G-SDI Wireless recording Monitor
screen

DI input/ 1* HDMI and SDI output / DC power input/ 3.5mm headphone jack/ SD card slot

›s battery + DC Input

›59.94/50/30/29.97/25/24/23.98

›59.94/50

›9.94/50

›le can't exceed 4G)

›7/33*33*33)

m

fe frames, grip, ratio marker, zoom, zebra, and many more

ales service card, TF Card, SD Card Holder, Tempered Screen Protector, HDMI Cable, SDI Cable,
onitor, After-sales service card, TF Card, SD Card Holder, Tempered Screen Protector, User Manual

› monitoring via the Shimbol app

y transmit to two receivers and one app

to 1080p60 HDMI and SDI video

line-of-sight transmission to receiver

v 0.08s Latency







1080 Touchscreen 3D Lut 4K HDMI Video Recording Monitor
screen

1* HDMI output / DC power input/ 3.5mm headphone jack/ TF card slot
+ 3.5 battery (without battery inside) + DC Input

24/23.98

23.98/25/24/23.98

59.94/50/30/29.97/25/24/23.98

59.94/50

59.94/50

file can't exceed 3.6G)
7/33*33*33)

5

ife frames, grip, ratio marker, zoom, zebra, and many more
red Screen Protector, HDMI Cable, Hot Shoe Mount, User Manual



h 1920*1080 Touchscreen 3D Lut 4K HDMI 3G-SDI Video Recording Monitor with 3D-LUT OUT
creen

DI input/ 1* HDMI+ SDI output / DC power input/ 3.5mm headphone jack/ SD card slot
s battery (without battery inside) + DC Input

24/23.98

23.98/25/24/23.98

59.94/50/30/29.97/25/24/23.98

59.94/50

59.94/50


file can't exceed 3.6G)

7/33*33*33)

5

fe frames, grip, ratio marker, zoom, zebra, and many more

rd, Tempered Screen Protector, HDMI Cable, SDI Cable, Hot Shoe Mount, Color Box, User Manual



1920*1080 Touchscreen 3D Lut 4K HDMI 3G-SDI Video Recording Monitor with 3D-LUT OUT

een

SDI input/ 1* HDMI+ SDI output / **SDI Input convert to HDMI output** / DC power input/ 3.5mm headphone jack/ SD card slot

24/23.98

23.98/25/24/23.98

59.94/50/30/29.97/25/24/23.98

59.94/50

59.94/50

format is exFAT)

7*17, 33*33*33)

series battery (without battery inside) + DC Input

support

alloy

0.3/28.3mm

Form # RGB Parade # Vectorscope # Histogram # The aspect ratio markers # Safe Area # Center Marker # Focus Peaking # Zoom In # Zebra Pattern # False Color # Monochrome, SD Card Carry Case, Tempered Screen Protector, Dusting Cloth, HDMI Cable, SDI Cable, Hot Shoe Mount, Color Box, User Manual

Additional on-camera monitor, 1920*1080 2000 nits, Touchscreen, 3D Lut, 4K HDMI + 3G SDI, Metal Frame
Screen

1* HDMI output / DC power input / 3.5mm headphone jack / SD card slot

24/23.98

23.98/25/24/23.98

59.94/50/30/29.97/25/24/23.98

59.94/50

59.94/50

7*17, 33*33*33)

Rechargeable battery (without battery inside) + DC Input

Support

1e

5mm

orm # RGB Parade # Vectorscope # Histogram # The aspect ratio markers # Safe Area # Center Marker # Focus Peaking # Zoom In # Zebra Pattern # False Color # Monochr
rd, Tempered Screen Protector, HDMI Cable, Hot Shoe Mount, User Manual

nal on-camera monitor, 1920*1080 2000 nits, Touchscreen , 3D Lut, 4K HDMI + 3G SDI, Metal Frame
een

DI input/ 1* HDMI+ SDI output / DC power input/ 3.5mm headphone jack/ SD card slot

24/23.98

23.98/25/24/23.98

59.94/50/30/29.97/25/24/23.98

59.94/50

59.94/50

7*17, 33*33*33)

series battery (without battery inside) + DC Input

upport

alloy

0.3/28.3mm

orm # RGB Parade # Vectorscope # Histogram # The aspect ratio markers # Safe Area # Center Marker # Focus Peaking # Zoom In # Zebra Pattern # False Color # Monochr
rd, SD Card Carry Case, Tempered Screen Protector, Dusting Cloth, HDMI Cable, SDI Cable, Hot Shoe Mount, Color Box, User Manual

ome # 3D LUT loading & adjustment # Gamma setting # HDR monitoring # Color temperature setting # Sharpness # RGB adjustment, etc.

ome # 3D LUT loading & adjustment # Gamma setting # HDR monitoring # Color temperature setting # Sharpness # RGB adjustment, etc.

ome # 3D LUT loading & adjustment # Gamma setting # HDR monitoring # Color temperature setting # Sharpness # RGB adjustment, etc.